# Aluminum Adjustable Height Gantry Crane with Pneumatic Casters 8 Ft. Wide x 8 Ft. Max Usable Height 1,500 Lb. Capacity Silver

**MODEL AHA-15-8-8-PNU**

Overhead Lifting / Adjustable Height Aluminum Gantry Cranes with Pneumatic Casters



## PRODUCT OVERVIEW

The adjustable height Aluminum Gantry crane combines a lightweight, rigid, and sturdy construction into one unit. The all aluminum construction of this gantry crane makes it corrosion resistant and perfect for outdoor use. Included are two (2) straps, allowing the gantry crane to be transported in one neat package.

## KEY FEATURES

- Heavy-duty welded aluminum construction
- Pinned connections for quick set up and take down
- Easily adjustable height with fork truck or other overhead lifting device
- Smooth rolling with four swivel pneumatic casters

## CORE PRODUCT DATA

| | | |
|---|---|---|
| ASSEMBLED WEIGHT<br>**206 lbs** | ASSEMBLED SIZE<br>**53.75" W x 96" L x 110.25" H** | SHIP WEIGHT<br>**254 lbs** |
| PACKAGE 1 SIZE<br>**29" W x 92" D x 18" H** | COLOR / FINISH<br>**Silver** | FREIGHT TYPE<br>**LTL Palletized** |

**AVAILABILITY** Available **QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Uniform Capacity (lb.)** | 1,500 |
| **Overall I-Beam Length (ft.)** | 8 |
| **I-Beam Height (In.)** | 6 |
| **I-Beam Flange Width (in.)** | 3-5/16 |
| **Under I-Beam Range (in.)** | 74 to 104 |
| **Base Width (in.)** | 53-3/4 |
| **Caster Quantity/Diameter/Width (in.)** | (4) 12 x 3-1/2 |
| **Caster Type** | Four-way locking |
| **Caster Material** | Pneumatic Rubber |
| **Usable Trolley Travel Distance (in.)** | 72-1/4 |
| **Increment Height Adjustment (in.)** | 6 |
| **Standards** | ASME B30.17 |
| **Compliance** | OSHA 29 CRF 1910.179 |
| **CalOSHA** | Exempt |

## PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

**AVAILABLE PRODUCT RESOURCES**

**SCAN FOR CURRENT PRODUCT DATA**

Live product page: https://www.vestil.com/product.php?EID=523