

Galvanized Alternate Tread Stair 56 Degrees 89-3/4 In. x 23-1/2 In. x 162-3/8 In. 350 Lb. Capacity Silver

MODEL ATS-10-56-HDG

Industrial Ladders / Alternating-Tread Stairs



PRODUCT OVERVIEW

Alternating-tread stair design is a great addition to a variety of warehouses and workshops. The unique design offers a shorter span than traditional steps. With a handrail on each side of unit and a dual safety chain at the top of the stair, security is the top priority of this ladder style.

KEY FEATURES

- Two-sided hand railing provides added user safety
- Steps are constructed of a raised steel surface providing better traction
- Handrails have a safety yellow powder coat finish
- Steel steps & platform have a durable hot dip galvanized finish

CORE PRODUCT DATA

ASSEMBLED WEIGHT
253 lbs

ASSEMBLED SIZE
162.375" W x 89.75" L x 23.5" H

SHIP WEIGHT
312 lbs

PACKAGE 1 SIZE
32" W x 151" D x 16" H

COLOR / FINISH
Silver

FREIGHT TYPE
LTL Palletized

AVAILABILITY Quote Required - Please Contact Sales

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	350
Number of Steps (Including Top Step)	16
Top Step Height (in.)	120
Step Angle (degrees)	56
Safety Chain (in.)	3/16
Top Step Depth (in.)	9-3/4
Top Step Width (in.)	23-5/8
Step (excluding top step) Depth (in.)	10-1/2
Step (excluding top step) Width (in.)	9-1/8
Step Height Spacing (in.)	7-1/2
Handrail Height (in.)	18-5/8
OSHA	29 CFR 1910.25(e`)

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA