Galvanized Alternate Tread Stair 56 Degrees 114-1/8 In. x 23-1/2 In. x 198-5/8 In. 350 Lb. Capacity Silver

MODEL ATS-13-56-HDG

Industrial Ladders / Alternating-Tread Stairs



PRODUCT OVERVIEW

Alternating-tread stair design is a great addition to a variety of warehouses and workshops. The unique design offers a shorter span than traditional steps. With a handrail on each side of unit and a dual safety chain at the top of the stair, security is the top priority of this ladder style.

KEY FEATURES

- Two-sided hand railing provides added user safety
- Steps are constructed of a raised steel surface providing better traction
- Handrails have a safety yellow powder coat finish
- Steel steps and platform have a durable hot dip galvanize finish

CORE PRODUCT DATA

ASSEMBLED WEIGHT **354 lbs**	ASSEMBLED SIZE **23.5" W x 114.125" L x 198.625" H**	SHIP WEIGHT **608 lbs**
PACKAGE 1 SIZE **33" W x 184" D x 19" H**	COLOR / FINISH **Silver**	FREIGHT TYPE **LTL Palletized**

AVAILABILITY Quote Required - Please Contact Sales **QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	350
Number of Steps	21
Top Step Height (in.)	156-1/4
Step Angle (degrees)	56
Safety Chain (in.)	3/16
Top Step Depth (in.)	9-3/4
Top Step Width (in.)	23-5/8
Step (excluding top step) Depth (in.)	10-1/2
Step (excluding top step) Width (in.)	9-1/8
Step Height Spacing (in.)	7-7/16
Handrail Height (in.)	18-5/8
OSHA	29 CFR 1910.25(e`)
Overall Height (in.)	198-5/8
Overall Length (in.)	114-1/8
Overall Width (in.)	23-1/2
Top Step Height (in.)	156-1/4

PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

AVAILABLE PRODUCT RESOURCES

SCAN FOR CURRENT PRODUCT DATA

Live product page: https://www.vestil.com/product.php?EID=612