

Steel Linear Elevating Cart 23-5/8 In. x 35-1/2 In. 400 Lb. Capacity Blue/Silver

MODEL CART-400-LA

Ergonomic Solutions / Linear Actuated Elevating Carts

PRODUCT OVERVIEW

The linear actuated elevating cart transports materials from workstation to workstation with ease. The platform is raised and lowered with an electric linear actuator for precise positioning. Linear actuator will not allow platform to drift down - a common problem with hydraulic carts. This linear actuated cart is powered by (2) 12v AGM batteries and feature bench type charger. Emergency stop button standard on control box. The units rolls smoothly on two rigid and two swivel casters. Features an internal safety velocity fuse in each cylinder.

KEY FEATURES

- Unique lift design quickly raises & lowers material
- Ergonomic cart design improves user safety
- Caster construction provides easy portability when loaded
- Steel construction offers long lasting rugged use

CORE PRODUCT DATA

ASSEMBLED WEIGHT
128 lbs

ASSEMBLED SIZE
44.5" W x 53.5" L x 42" H

SHIP WEIGHT
228 lbs

PACKAGE 1 SIZE
41" W x 49" D x 38" H

COLOR / FINISH
Blue

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	400
Platform Width (in.)	23-5/8
Platform Length (in.)	35-1/2
Lowered Height (in.)	15
Raised Height (in.)	34
Lowering Method	12 Volt Battery
Scissor Design	Single
Rear Caster Diameter (in.)	4
Rear Caster Width (in.)	2
Front Caster Diameter (in.)	4
Front Caster Width (in.)	2
Caster (quantity)	4
Caster Material	Poly-on-Steel
Front Caster Type	Swivel
Rear Caster Type	Rigid
Battery Quantity/Voltage	(2) 12V
Overall Length (in.)	53-1/2
Overall Width (in.)	44-1/2
Overall Height (in.)	42
Battery Depth	10
Battery Width	14
Battery Height	11
Battery Weight	10
Battery Freight Class	60
Battery NMFC Number	60700
Battery NMFC Description	Gel batteries on unit
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=277>