

Steel Commercial Circulating Pedestal Fan 24 In. Black/Silver

MODEL CCRF-24-P

Facilities Maintenance / Commercial Circulator Fans



PRODUCT OVERVIEW

The two speed commercial circulating is perfect for a variety of industries. The pull chain switch give the user functional control. These portable blowers do not have a totally enclosed motor. The guard is coated steel with retaining clips. The fan has a steel hub and aluminum paddle blades. The motor is permanently lubricated with a permanent split capacitor.

KEY FEATURES

- Meets OSHA standards and is UL C/US listed
- Three blade design keeps are moving
- Use in a clean and dry commercial application
- Wide circular pedestal base

CORE PRODUCT DATA

ASSEMBLED WEIGHT
63 lbs

ASSEMBLED SIZE
104" W x 27" L x 27" H

SHIP WEIGHT
63 lbs

PACKAGE 1 SIZE
8" W x 33" D x 35" H

COLOR / FINISH
Black / Silver

FREIGHT TYPE
Parcel

AVAILABILITY Quote Required - Please Contact Sales

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Blade Diameter (in.)	25
Mounting Style	Pedestal
Amps High	2.3
CFM High	5400
CFM Low	4300
Electric Motor Horsepower	1/4
Conductor Cord Length (in.)	108
Conductor Cord	SJT type 3
Voltage/Phase	120V/1PH
CFM Medium	4900
OSHA	1910.212 (a)(5)
Lowest Pole Position (in.)	43
Highest Pole Position (in.)	6

PRODUCT & SHIPPING REFERENCE

Shipping Point: Gary, TN 37615

Warranty: 90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA