Vinyl Dock Seal 20 In. 8 Ft. x 8 Ft. Black

MODEL D-150-20

Loading Dock Equipment / Dock Seals



PRODUCT OVERVIEW

The superior nylon reinforced vinyl facing has a higher tear strength than equivalent weight hypalon. The chemically sealed ends prevent moisture infiltration. It is mounted and bonded on a durable pressure treated wood and contains a full height air escape tunnel. The unit consists of a three (3) piece construction with beveled fronts and a through the wall installation kit that is included. Five inch (5") maximum compression is recommended. Application with a flush dock to building in conjunction with an Edge-O-Dock use a twenty (20) inch projection Dock Seal. To ensure proper size complete the survey sheet. This unit is non-returnable.

KEY FEATURES

- Three foam-filled pads offer full dock protection
- Maximum compression design offers the maximum protection
- Built-in air tunnels allow air to escape when contacted by a trailer
- Mounting hardware and installation instructions make installation quick and easy

CORE PRODUCT DATA

ASSEMBLED WEIGHT **140 lbs**	ASSEMBLED SIZE **120" W x 20" L x 108" H**	SHIP WEIGHT **252 lbs**
PACKAGE 1 SIZE **36" W x 120" D x 26" H**	COLOR / FINISH **Black**	FREIGHT TYPE **LTL Palletized**

AVAILABILITY Available **QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Projection (in.)	20
Nylon Reinforced Vinyl (oz.)	36
Nylon Reinforced Guide Strips (in.)	2
Top Height (in.)	12
Side Wall Width (in.)	9-1/2
Face Width (in.)	12
Maximum Compression (in.)	5
Standard Guide Stipe Height (in.)	30
Side Height (in.)	96
Max Door Width (in.)	96
Max Door Height (in.)	96

PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **90 Days**

AVAILABLE PRODUCT RESOURCES

SCAN FOR CURRENT PRODUCT DATA

Live product page: https://www.vestil.com/product.php?EID=19