
Steel Sliding Tilt Table 48 In. x 48 In. 4000 Lb. Capacity Blue

MODEL EHTT-L

Ergonomic Solutions / Hinge & Sliding Tilt Tables



PRODUCT OVERVIEW

The sliding tilt table offers the rugged durability of the standard efficiency master line of tilters, plus they offer an extra platform height. The lip is without side gussets allowing for loading and unloading on three sides. The sliding tilt table incorporates a patented sliding link-tilt design for maximum stability while occupying minimum space. As the table is tilted, the front edge of the container moves away from the operator. Side gussets are required when ordering optional accordion skirt.

KEY FEATURES

- Offers rugged durability of the standard master line plus extra platform height
- Features counterbalanced valves and modulated flow control for maximum efficiency
- Patented sliding link-tilt design for maximum stability while occupying minimum space
- Center-of-gravity of load remains closer to the center of the frame

CORE PRODUCT DATA


ASSEMBLED WEIGHT	ASSEMBLED SIZE	SHIP WEIGHT
648 lbs	48" W x 56" L x 44" H	770 lbs

PACKAGE 1 SIZE	COLOR / FINISH	FREIGHT TYPE
64" W x 66" D x 27" H	Blue	LTL Palletized


AVAILABILITY Available **QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

ADDITIONAL PRODUCT VIEWS







PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	4,000
Platform Width (in.)	48
Platform Length (in.)	47-3/4
Level Height (in.)	8
Maximum Tilt Degree	45
Lip Height (in.)	12
Motor Horsepower	2
Voltage/Phase	460/3 AC
Fork Pocket Width/Height (in.)	7-1/2 x 2-1/2
Fork Pocket Center (in.)	28
Overall Width (in.)	48
Overall Length (in.)	56
Overall Height (in.)	44
Extension Coil Cord Length (ft.)	8
Handheld Push Button Control	Yes

PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

AVAILABLE PRODUCT RESOURCES

SCAN FOR CURRENT PRODUCT DATA

Live product page: https://www.vestil.com/product.php?EID=214