

Steel Electric Powered Floor Crane 2500 Lb. Retracted Capacity Yellow

MODEL EPFC-25

Overhead Lifting / Electric Powered Floor Cranes



PRODUCT OVERVIEW

The fully powered electric floor crane has an easy and quick operation. The unit raises and lowers loads with the push of a button and can maneuver loads in warehouses and trailers. The heavy duty rigid hook with safety latch provides long service. The high-torque DC drive and lift motors handle heavy-duty jobs. Floor crane includes integral battery charger, battery level gauge, and emergency battery disconnect. The truck rolls smoothly on poly-on-steel, steer and load wheels. Ergonomic handle features easy to operate throttle with infinite adjustment of forward and reverse speeds, controlled lift/lower controls, adjustable length legs, proprietary safety-enhancing emergency reverse function, and horn. When the proprietary safety-enhancing emergen...

KEY FEATURES

- Fully-powered floor crane makes movement of material quick and easy
- Includes fingertip raise and lower buttons for operator convenience
- Safety belly reverse button improves worker safety
- Easy-to-operate throttle for forward and reverse direction with infinite speeds

CORE PRODUCT DATA

ASSEMBLED WEIGHT
865 lbs

ASSEMBLED SIZE
66.375" W x 79.5" L x 30" H

SHIP WEIGHT
1006 lbs

PACKAGE 1 SIZE
47" W x 89" D x 69" H

COLOR / FINISH
Yellow

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

QUICKSHIP: YES

PRODUCT SPECIFICATIONS

Uniform Capacity Retracted (lb.)	2,500
Uniform Capacity Boom Half-Way Extended (lb.)	1300
Uniform Capacity Boom Fully Extended (lb.)	600
Width Between Legs/Wheels - Retracted (in.)	23
Width Between Legs/Wheels - Extended (in.)	28
Manual Extension Holes (qty.)	3
Space Between Holes (in.)	8
Maximum Height - Crane Extended (in.)	110
Max. Length - Legs Extended (in.)	103-1/8
Lift Range - Retracted (in.)	44-1/4
Lift Range - Extended (in.)	94
Drive Motor	DC24V / 0.7KW
Lift Motor	DC24V / 2KW
Battery (quantity)	2
Battery Type	12V
Battery Charger	24V / 12 AMP
Battery Charger Power Cord	115V AC
Minimum Service Per Charge (hrs.)	8
Lift Speed w/o Load (seconds)	0.7
Lift Speed w/ Load (seconds)	0.5
Battery Charge Time (hrs.)	8
Charger Cord Length (in.)	62
Charger Plug Type	3 Prong
Specifications	ANSI Z535
Hook Material	Steel
Hook Opening (in.)	1-1/4
Wheel Material	Poly
Front Wheel Quantity/Configuration	2/Rigid

4 additional technical attributes are available on the live Vestil product page.

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA