

Steel Electric Powered Counter Balanced Floor Crane 1500 Lb. Retracted Capacity Yellow

MODEL EPFC-CB-15

Overhead Lifting / Electric Powered Floor Cranes

PRODUCT OVERVIEW

Fully powered shop cranes (power hoist & power in/out boom) for moving loads quickly, easily, and safely. 24V DC drive and lift motor handles heavy-duty jobs. The ergonomic handle features an easy-to-operate throttle with infinite adjustment of forward and reverse speeds, lift/lower controls, proprietary safety-enhancing emergency reverse function, and horn. It includes an electromagnetic disc brake with automatic dead-man feature that activates when user releases the handle. The powered shop crane has two (2) 12V batteries, an integral battery charger, and a battery level gauge. Batteries capable of 3-4 hour operation at full charge, with up to 8 hours when used intermittently. Features also include poly-on-steel steer and load wheels and a rigid...

KEY FEATURES

- Counter balance design for heavy lifting
- Fixed legs for constant size
- Emergency reverse belly switch instantly reverses direction
- Stand up user design for quick action

CORE PRODUCT DATA

ASSEMBLED WEIGHT
1598 lbs

ASSEMBLED SIZE
68.375" W x 107.5" L x 33.875" H

SHIP WEIGHT
1888 lbs

PACKAGE 1 SIZE
47" W x 106" D x 70" H

COLOR / FINISH
Yellow

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity Retracted (lb.)	1,500
Uniform Capacity Boom Half-Way Extended (lb.)	800
Uniform Capacity Boom Fully Extended (lb.)	400
Maximum Height - Crane Extended (in.)	105
Lift Range - Retracted (in.)	44-1/4
Lift Range - Extended (in.)	97
Drive Motor	DC24V / 0.7KW
Lift Motor	DC24V / 2KW
Battery (qty.)	2
Battery Type	12V
Battery Charger	24V / 12 amp
Battery Charger Power Cord	115V AC
Minimum Service Per Charge (hrs.)	8
Lift Speed w/o Load (sec)	0.7
Lift Speed w/ Load (sec)	0.5
Lower down speed w/o load (sec)	0.25
Lower down speed w/ Load (sec)	0.75
Travel speed w/o load (mph)	2.8
Travel speed w/load (mph)	2.18
Battery Depth	11
Battery Width	14
Battery Height	9
Battery Weight	84
Battery Freight Class	70
Battery NMFC Number	60680
Battery NMFC Description	UN2794 BATTERIES WET FILLED WITH ACID
Battery Subclass	1
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=586>