

Steel Fully Powered Electric Pallet Truck 20 In. x 48 In. 4,500 Lb. Capacity Black

MODEL EPT-2048-45

Ergonomic Solutions / Fully Powered Electric Pallet Trucks

PRODUCT OVERVIEW

The fully powered electric pallet truck has an easy and quick operation. The unit raises and lowers loads with a push of a button. It can maneuver loads in warehouses and trailers. The reinforced welded forks have adjustable tie-rods that provide long service. The high-torque DC drive and lift motors handle heavy-duty jobs. Unit includes integral battery charger, battery level gauge, and emergency battery disconnect. The truck rolls smoothly on poly-on-steel, steer and load wheels. Ergonomic handle features easy to operate throttle with infinite adjustment of forward and reverse speeds, lift/lower controls, proprietary safety-enhancing emergency reverse function, and horn. When the proprietary safety-enhancing emergency reverse function is actuate...

KEY FEATURES

- Fully-powered pallet truck makes movement of pallets quick and easy
- Includes fingertip raise and lower buttons for operator convenience
- Safety belly reverse button improves worker safety
- Easy-to-operate throttle for forward and reverse direction

CORE PRODUCT DATA

ASSEMBLED WEIGHT
1021 lbs

ASSEMBLED SIZE
30.25" W x 76" L x 51.4375" H

SHIP WEIGHT
1076 lbs

PACKAGE 1 SIZE
44" W x 90" D x 63" H

COLOR / FINISH
Black / Yellow

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Overall Fork Width (in.)	20.5
Overall Fork Length (in.)	48
Uniform Capacity (lb.)	4500
Lowered Height (in.)	3.4
Raised Height (in.)	7.8
Battery Type	(4) 6 Volt
DC Motor Voltage	24
Battery Charger	120V Input, 24V/20 amp
Turn Radius (in.)	52
Drive KW	1.2
Lift Motor KW	1.3
Operation at Full Charge (hours)	6 to 7
Operation When Used Intermittently (hours)	8
Drive Wheel Diameter (in.)	10
Drive Wheel Width (in)	3-1/8
Load Roller Diameter (in.)	2-3/4
Load Roller Width (in.)	3
Stabilizing Roller Diameter (in.)	1-1/2
Stabilizing Roller Width (in.)	3
Wheel & Roller Type	Poly on Steel
Battery Depth	22
Battery Width	21
Battery Height	11
Battery Weight	248
Battery Freight Class	70
Battery NMFC Number	60680
Battery NMFC Description	UN2794 BATTERIES WET FILLED WITH ACID
Battery Subclass	1

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?EID=342>