

Steel Electric Pallet Truck with Scale 25 In. x 47 In. 3000 Lb. Capacity Black / Yellow

MODEL EPT-2547-30-SCL

Ergonomic Solutions / Electric Pallet Trucks with Scale

PRODUCT OVERVIEW

The electric pallet truck with scale can verify inbound and outbound freight right on your pallet truck and then move your loads with ease. The LCD scale and function keys (zero, tare, net/gross, print, LB/KG), displays weight in one (1) pound increments within trucks rated capacity. The scale display operates on AA batteries (best accuracy is 0.01 percent of maximum calibrated weight). The scale is not NTEP approved (not legal for trade). Scale head includes RS232 port for serial printing. An individual can raise and lower loads with a push of a button. The unit makes it easy to maneuver loads in warehouses and trailers. Reinforced welded forks with adjustable tie-rods provide long service. The high torque DC drive and lift motor handles heavy du...

KEY FEATURES

- Fully-powered pallet truck makes movement of pallets quick and easy
- Includes fingertip raise and lower buttons for operator convenience
- Safety belly reverse button improves worker safety
- Easy-to-operate throttle for forward and reverse direction

CORE PRODUCT DATA

ASSEMBLED WEIGHT
662 lbs

ASSEMBLED SIZE
28.25" W x 66.125" L x 49.21" H

SHIP WEIGHT
706 lbs

PACKAGE 1 SIZE
42" W x 85" D x 57" H

COLOR / FINISH
Black & Yellow

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

QUICKSHIP: YES

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	3,000
Service Range (in.)	3-3/8 to 8
Fork Width x Length (in.)	6-11/16 x 48
Fork Spacing (in.)	25-9/16
Drive Wheel Width/Diameter (in.)	3-1/8 x 10
Load Roller Width/Diameter (in.)	3 x 2-3/4
Turn Radius (in.)	52
Battery Charger	120V Input, 24V/10 amp
Battery Qty./Type	(2) 12V FLA (Flooded Lead Acid)
Drive Motor KW	0.7
Lift Motor KW	1.3
Operation Time with Full Charge (hours)	3 to 4 hours
Operation Time with Intermittent Use	8 hours
Battery Depth	21
Battery Width	14
Battery Height	9
Battery Weight	83
Battery Freight Class	70
Battery NMFC Number	60680
Battery NMFC Description	UN2794 BATTERIES WET FILLED WITH ACID
Battery Subclass	1
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA