

# Steel Electric Pallet Truck with Scale 27 In. x 48 In. 4500 Lb. Capacity Black / Yellow

MODEL EPT-2748-45-SCL

Ergonomic Solutions / Electric Pallet Trucks with Scale



## PRODUCT OVERVIEW

The electric pallet truck with scale can verify inbound and outbound freight right on your pallet truck and then move your loads with ease. The LCD scale and function keys (zero, tare, net/gross, print, LB/KG), displays weight in 1 pound increments within trucks rated capacity. The scale display operates on AA batteries (best accuracy is 0.01 percent of maximum calibrated weight). The scale is not NTEP approved (not legal for trade). Scale head includes RS232 port for serial printing. An individual can raise and lower loads with a push of a button. The unit makes it easy to maneuver loads in warehouses and trailers. Reinforced welded forks with adjustable tie-rods provide long service. The high torque DC drive and lift motor handles heavy duty job...

## KEY FEATURES

- Fully-powered pallet truck makes movement of pallets quick and easy
- Includes fingertip raise and lower buttons for operator convenience
- Safety belly reverse button improves worker safety
- Easy-to-operate throttle for forward and reverse direction

## CORE PRODUCT DATA

ASSEMBLED WEIGHT  
**1056 lbs**

ASSEMBLED SIZE  
**30.1875" W x 76.5" L x 51.375" H**

SHIP WEIGHT  
**1206 lbs**

PACKAGE 1 SIZE  
**46" W x 89" D x 60" H**

COLOR / FINISH  
**Black / Yellow**

FREIGHT TYPE  
**LTL Palletized**

AVAILABILITY Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

QUICKSHIP: YES

## ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

|                                      |                                       |
|--------------------------------------|---------------------------------------|
| Uniform Capacity (lb.)               | 4,500                                 |
| Fork Width x Length (in.)            | 7-1/16 x 48                           |
| Fork Spacing (in.)                   | 27                                    |
| Service Range (in.)                  | 3-3/8 to 8                            |
| Battery Qty./Type                    | (4) 6V FLA (Flooded Lead Acid)        |
| DC Motor Voltage                     | 24                                    |
| Battery Charger                      | 120V Input, 24V/20 amp                |
| Drive KW                             | 1.2                                   |
| Lift Motor KW                        | 2.0                                   |
| Turn Radius (in.)                    | 69                                    |
| Operation Time with Full Charge      | 6 to 7 hours                          |
| Operation Time with Intermittent Use | 8 hours                               |
| Drive Wheel Diameter/Width (in.)     | 10 x 3-1/8                            |
| Load Roller Diameter/Width (in.)     | 2-3/4 x 3                             |
| Scale Accuracy                       | 0.1% of Applied Load                  |
| Battery Depth                        | 22                                    |
| Battery Width                        | 21                                    |
| Battery Height                       | 11                                    |
| Battery Weight                       | 248                                   |
| Battery Freight Class                | 70                                    |
| Battery NMFC Number                  | 60680                                 |
| Battery NMFC Description             | UN2794 BATTERIES WET FILLED WITH ACID |
| Battery Subclass                     | 1                                     |
| Lithium Battery Configuration        | C -- Contained In                     |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA