Steel Electric Pallet Truck with Scale and Rider Platform 27 In. x 48 In. 4500 Lb. Capacity Yellow/Black

MODEL EPT-2748-45-SCL-RP

Ergonomic Solutions / Electric Pallet Trucks with Scale



PRODUCT OVERVIEW

The electric pallet truck with scale can verify inbound and outbound freight right on your pallet truck and then move your loads with ease. The LCD scale and function keys (zero, tare, net/gross, print, LB/KG), displays weight in 1 pound increments within trucks rated capacity. The scale display operates on AA batteries (best accuracy is 0.01 percent of maximum calibrated weight). The scale is not NTEP approved (not legal for trade). Scale head includes RS232 port for serial printing. An individual can raise and lower loads with a push of a button. The unit makes it easy to maneuver loads in warehouses and trailers. Reinforced welded forks with adjustable tie-rods provide long service. The high torque DC drive and lift motor handles heavy duty job...

KEY FEATURES

- Fully-powered pallet truck makes movement of pallets quick and easy
- Includes fingertip raise and lower buttons for operator convenience
- Safety belly reverse button improves worker safety
- Easy-to-operate throttle for forward and reverse direction

CORE PRODUCT DATA

ASSEMBLED WEIGHT **1056 lbs**	ASSEMBLED SIZE **30.25" W x 76.5" L x 51.375" H**	SHIP WEIGHT **954 lbs**
PACKAGE 1 SIZE **42" W x 85" D x 57" H**	COLOR / FINISH **Black / Yellow**	FREIGHT TYPE **LTL Palletized**

AVAILABILITY Available **QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	4,500
Fork Width x Length (in.)	7-1/16 x 48
Fork Spacing (in.)	27
Service Range (in.)	3-3/8 to 8
Battery Qty./Type	(4) 6V FLA (Flooded Lead Acid)
DC Motor Voltage	24
Battery Charger	120V Input, 24V/20 amp
Drive Motor KW	1.2
Lift Motor KW	2.0
Turn Radius (in.)	78-3/8
Operation Time with Full Charge	6 to 7 hours
Operation Time with Intermittent Use	8 hours
Drive Wheel Diameter/Width (in.)	10 x 3-1/8
Load Roller Diameter/Width (in.)	2-3/4 x 3
Scale Accuracy	0.1% of Applied Load
Battery Depth	22
Battery Width	21
Battery Height	11
Battery Weight	248
Battery Freight Class	70
Battery NMFC Number	60680
Battery NMFC Description	UN2794 BATTERIES WET FILLED WITH ACID
Battery Subclass	1
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

AVAILABLE PRODUCT RESOURCES

SCAN FOR CURRENT PRODUCT DATA

Live product page: https://www.vestil.com/product.php?EID=343