# Steel Stationary Hydraulic Drum Dumper 72 In. Dump Height 750 Lb. Capacity Blue / Yellow

**MODEL HDD-72-7-S**

Drum Handling Equipment / Hydraulic Drum Dumpers



## PRODUCT OVERVIEW

The Hydraulic drum dumper is what you need to dump heavy drums. Works with plastic, steel, and fiber drums. Dumper has a solid steel chute and all steel construction. Upper travel limit switch, emergency brass safety velocity fuse in cylinder, and vertical adjustment drum restraints are standard. Dumper is operated with a hand held control on a coil cord standard.

## KEY FEATURES

- Internal pre-wired heavy-duty electric motor conveniently dumps drums
- Adjustable drum restraints work with all types of 30 and 55 gallon drums
- Drum rotation design may be stopped at any point
- Solid steel construction offers long lasting reliable use

## CORE PRODUCT DATA

| ASSEMBLED WEIGHT | ASSEMBLED SIZE | SHIP WEIGHT |
|---|---|---|
| 875 lbs | 36" W x 92" L x 95.25" H | 1040 lbs |

| PACKAGE 1 SIZE | COLOR / FINISH | FREIGHT TYPE |
|---|---|---|
| 44" W x 96" D x 89" H | Blue (Frame), Yellow (Chute) | LTL Palletized |

**AVAILABILITY** Available **QUICKSHIP: --**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Uniform Capacity (lb.)** | 750 |
| **Dump Height (in.)** | 72 |
| **Rotated Height (in.)** | 157-1/2 |
| **Level Height (in.)** | 95-1/4 |
| **Accepts** | 30 and 55-gallon drums |
| **Motor Horsepower** | 3/4 |
| **Single Phase (volts)** | 115 |
| **Motor (Hz)** | 60 |
| **Power Cord Length (ft.)** | 8 |
| **Hand Held Control Cord Length (ft.)** | 8 |
| **Drum Rotation (deg.)** | 135 |
| **Dump Angle (deg.)** | 45 |
| **Chute Diameter (in.)** | 24 |
| **Raise Time (sec.)** | 34 |
| **Motor Style** | 56 Frame |
| **Cylinder Diameter (in.)** | 2-1/2 |
| **Cylinder Length (in.)** | 18 |
| **Chute Reach (in.)** | 13-1/2 |
| **Accepted Drum Diameter (in.)** | 16.5 to 23.5 |
| **Accepted Drum Height (in.)** | 27.5 to 39.5 |

## PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

**AVAILABLE PRODUCT RESOURCES**

**SCAN FOR CURRENT PRODUCT DATA**

Live product page: https://www.vestil.com/product.php?FID=766