


# Steel Rolling Warehouse Ladder 50 Degree 13 Perforated 23-9/16 In. Step Width 350 Lb. Capacity Blue

**MODEL LAD-13-14-P-EZ**

Industrial Ladders / Rolling Warehouse Ladders (12-16 Step)



## PRODUCT OVERVIEW

The rolling warehouse ladder is a great addition to material handling and shipping facilities. The powder coated steel construction maintains a strong, durable design throughout a lifetime of use. The steps include a perforated design and a 50 degrees climb angle that promotes stability while climbing and/or descending the ladder. The bottom step is colored yellow for additional safety and minimization of injuries when traversing the ladder with heavy loads.

## KEY FEATURES

- Steel construction for lasting durability
- Perforated steps for safe traversing
- Rolling design for maneuvering in condensed areas
- Bottom step is colored yellow for utmost safety

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**368 lbs**

**ASSEMBLED SIZE**  
**166" W x 120.875" L x 42.25" H**

**SHIP WEIGHT**  
**450 lbs**

**PACKAGE 1 SIZE**  
**60" W x 157" D x 24" H**

**COLOR / FINISH**  
**Blue**

**FREIGHT TYPE**  
**LTL Palletized**

**AVAILABILITY**      Available

**QUICKSHIP:** --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

|                                                  |              |
|--------------------------------------------------|--------------|
| Uniform Capacity (lb.)                           | 350          |
| Number of Steps (qty.)                           | 13           |
| Step Angle (degrees)                             | 50           |
| Top Step Height (in.)                            | 130          |
| Top Step Depth (in.)                             | 14           |
| Step Depth (in.)                                 | 7            |
| Usable Width (in.)                               | 23-9/16      |
| Usable Length (in.)                              | 116-9/16     |
| Step Type                                        | Perforated   |
| Step Spacing (in.)                               | 10           |
| Front Swivel Poly Caster Quantity/Diameter/Width | (2) 3x1-1/4  |
| Rear Rigid Hard Rubber Caster Quantity/Diameter  | (2) 10x2-1/2 |
| OSHA                                             | 1910.29      |
| ANSI                                             | A14.7        |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=1399>