

# Steel Telescoping Lift Boom 24 In. Fork Pocket Center 8,000 Lb. Capacity Blue and Yellow

**MODEL LM-1T-8-24**

Fork Truck Attachments / Lift Master Fork Truck Booms



## PRODUCT OVERVIEW

The lift boom delivers heavy-duty performance, maximum operator convenience, and uncompromising safety in challenging manufacturing and warehouse environments. Fabricated from high-strength structural steel and welded to rigorous AWS standards, this rugged, durable unit is engineered for years of reliable, long-term service. For precision operation, it features an infinitely adjustable locking screw alongside a robust safety restraint that secures the boom directly to the fork truck to ensure secure, slip-free performance. Ready for immediate use, each unit comes fully equipped with two high-capacity lifting hooks to maximize your facility's material handling efficiency.

## KEY FEATURES

- Unique design converts fork trucks into overhead lifting cranes
- Fork pockets with safety strap attach & secure boom to fork truck
- Robotically welded construction provides precision and durability
- Operations & capacity sticker provide user instructions and safety

## CORE PRODUCT DATA

**ASSEMBLED WEIGHT**  
**647 lbs**

**ASSEMBLED SIZE**  
**32" W x 84.625" L x 26.5625" H**

**SHIP WEIGHT**  
**647 lbs**

**PACKAGE 1 SIZE**  
**32" W x 86" D x 27" H**

**COLOR / FINISH**  
**Blue (Base Frame)/Yellow (Extension)**

**FREIGHT TYPE**  
**LTL Loose**

**AVAILABILITY**      Available

**QUICKSHIP:** --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

## ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

|                                    |                  |
|------------------------------------|------------------|
| Uniform Capacity (lb.)             | 8,000            |
| Fork Pocket Center (in.)           | 24               |
| Fork Pocket Width/Height (in.)     | 7-1/4 x 2-1/4    |
| Restraint Length (in.)             | 36               |
| Boom Style                         | Telescoping      |
| Minimum/Maximum Hook Point (in.)   | 36/144           |
| Single-Hook Capacity at 36" (lb.)  | 8000             |
| Single-Hook Capacity at 48" (lb.)  | 6650             |
| Single-Hook Capacity at 60" (lb.)  | 6000             |
| Single-Hook Capacity at 72" (lb.)  | 5300             |
| Single-Hook Capacity at 84" (lb.)  | 4650             |
| Single-Hook Capacity at 96" (lb.)  | 4000             |
| Single-Hook Capacity at 108" (lb.) | 3500             |
| Single-Hook Capacity at 120" (lb.) | 3000             |
| Single-Hook Capacity at 132" (lb.) | 2600             |
| Single-Hook Capacity at 144" (lb.) | 2200             |
| Overall Extended Length (in.)      | 149-1/8          |
| Boom Type                          | Lift Master Boom |
| OSHA                               | 1910.178(a)(4)   |
| Overall Width (in.)                | 32               |
| Overall Height (in.)               | 26-9/16          |
| Overall Length Retracted (in.)     | 84-5/8           |

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=473>