# Steel Traction Drive Cart Side Load 1 Shelf 59 In. x 28 In. x 44 In. 750 Lb. Capacity Black

**MODEL NE-CART-3**

Industrial Carts & Dollies / Traction-Drive Carts



## PRODUCT OVERVIEW

This traction-drive cart features built-in traction-drive system for easy transportability. Ideal for applications including mail rooms, hospitals, supermarkets, hotels and warehouses. Features electric drive motor with batteries for power. Internal battery charger is included. Variable throttle speed control for precise maneuvering and positioning is located in the handle. Speed control is conveniently located in handle. Handle pivots back towards operator and includes horn, automatic brake and emergency stop. Each shelf includes a non-slip tread plate surface. Includes on-board charger and battery level indicator.

## KEY FEATURES

- Each shelf includes a non-slip tread plate surface
- Emergency safety stop belly-bump button switch provides added user safety
- Cart rolls smoothly on non-marking solid foam filled wheels
- Battery level indicator signals user when battery gets low

## CORE PRODUCT DATA

| | | |
|---|---|---|
| ASSEMBLED WEIGHT<br>**429 lbs** | ASSEMBLED SIZE<br>**28" W x 59" L x 44" H** | SHIP WEIGHT<br>**395 lbs** |
| PACKAGE 1 SIZE<br>**40" W x 64" D x 53" H** | COLOR / FINISH<br>**Black** | FREIGHT TYPE<br>**LTL Palletized** |


**AVAILABILITY** Available **QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

### ADDITIONAL PRODUCT VIEWS









## PRODUCT SPECIFICATIONS

| | |
|---|---|
| **Overall Capacity (lb.)** | 750 |
| **Shelf Capacity (lb.)** | 250 |
| **Platform Length (in.)** | 46 |
| **Platform Width (in.)** | 24-3/4 |
| **Deck Height (in.)** | 14 |
| **Shelf Height (in.)** | 33 |
| **Distance Between Platforms (in.)** | 17-3/4 |
| **Steering Wheel Diameter (in.)** | 9 |
| **Steering Wheel Width (in.)** | 3-1/4 |
| **Number of Steering Wheels** | 2 |
| **Steering Wheel Type** | Solid Foam Tires |
| **Drive Wheel Diameter (in.)** | 10 |
| **Drive Wheel Width (in.)** | 3-1/4 |
| **Number of Drive Wheels** | 2 |
| **Drive Wheel Type** | Solid Foam Tires |
| **Handle Height (in.)** | 44-11/16 |
| **Railing Height (in.)** | 40 |
| **Fast Travel Speed Loaded (miles per hour)** | 2.5 |
| **Fast Travel Speed Unloaded (miles per hour)** | 2.8 |
| **Slow Travel Speed Loaded (miles per hour)** | 1.3 |
| **Battery Depth** | 11 |
| **Battery Width** | 14 |
| **Battery Height** | 9 |
| **Battery Weight** | 84 |
| **Battery Freight Class** | 70 |
| **Battery NMFC Number** | 60680 |
| **Battery NMFC Description** | UN2794 BATTERIES WET FILLED WITH ACID |
| **Battery Subclass** | 1 |

## PRODUCT & SHIPPING REFERENCE

Shipping Point: **Angola, IN 46703**

Warranty: **1 Year**

**AVAILABLE PRODUCT RESOURCES**

**SCAN FOR CURRENT PRODUCT DATA**

Live product page: https://www.vestil.com/product.php?EID=1024