

Steel Hand Pump Edge-O-Dock Leveler 72 In. Ramp Width x 36-5/8 In. Ramp Length 25,000 Lb. Capacity Brown

MODEL PP-2572-36

Loading Dock Equipment / Edge-O-Dock Levelers

PRODUCT OVERVIEW

The Edge-O-Dock leveler permanently attaches to face of dock. It is recommended for docks to be at least 48 inches high. When the trailer departs, the lip drops automatically behind the face of the bumpers. It comes complete with bumpers and installation instructions. Standard ramping is 29 inches; models FM/PP/PE 3066 and 3072 are 29-13/16 inches, with a 36-5/8 inches long ramping length available. A steel dock edge, or approach ramp is required for proper installation. The Hydraulic hand pump system is used to lift the leveler and extend the lip. The operator rotates the relief valve allowing the deck to descend down and rest upon the trailer. Unit comes complete with hand pump, wall mount brackets, cylinder, one-hundred eighty (180) inch hydrau...

KEY FEATURES

- Easy install allows unit to quickly mount to any loading dock with a steel dock edge
- Tread plate design offers a positive non-slip gripping action
- Product design conveniently does not require a concrete recess
- Solid steel construction offers long lasting reliable use

CORE PRODUCT DATA

ASSEMBLED WEIGHT
749 lbs
ASSEMBLED SIZE
98" W x 26.75" L x 27.75" H
SHIP WEIGHT
780 lbs
PACKAGE 1 SIZE
15" W x 72" D x 38" H
COLOR / FINISH
Brown
FREIGHT TYPE
LTL Loose
AVAILABILITY Available

QUICKSHIP: --

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	25,000
Service Range Above Dock (in.)	5
Service Range Below Dock (in.)	5
Bumper Width (in.)	8
Bumper Length (in.)	2
Bumper Height (in.)	18
Ramp Width (in.)	72
Ramping Length (in.)	36-5/8
Bumper projection including rubber bumper (in.)	26-3/4

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA