

Steel Adjustable Powered Lift Stacker 150 In. Raised Height 2000 Lb. Capacity Black / Yellow

MODEL S-150-AA

Ergonomic Solutions / Stackers with Powered Drive and Powered Lift



PRODUCT OVERVIEW

The stacker with powered drive and powered lift is a fully powered electric stacker that transports loads throughout warehouse facilities quickly and with less effort. The high torque drive and lift motor handles heavy-duty jobs. The ergonomic handle features easy-to-operate throttle with infinite adjustment of forward and reverse speeds, lift/lower controls, proprietary safety-enhancing emergency reverse function, and horn. When the proprietary safety-enhancing emergency reverse function is actuated, the emergency reverse belly switch instantly reverses direction and moves the unit forward (away from the operator) until the switch is released or after five seconds have elapsed. The built-in safety circuit will automatically disable the entire unit...

KEY FEATURES

- High torque drive and lift motor handles heavy-duty jobs
- Ergonomic handle features easy-to-operate throttle
- Emergency reverse belly switch instantly reverses direction
- Operator protection is unmatched by any unit on the market

CORE PRODUCT DATA

ASSEMBLED WEIGHT
1290 lbs

ASSEMBLED SIZE
57.875" W x 68.875" L x 171.8125" H

SHIP WEIGHT
1548 lbs

PACKAGE 1 SIZE
64" W x 78" D x 102" H

COLOR / FINISH
Black / Yellow

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

QUICKSHIP: YES

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Uniform Capacity at 0 - 62" (lb.)	2,000
Uniform Capacity at 62 - 118" (lb.)	1,500
Uniform Capacity at 118 - 137" (lb.)	1,000
Uniform Capacity at 137 - 150" (lb.)	750
Service Range (in.)	2-1/8 to 118
Fork Width/Length (in.)	4 x 42-1/4
Adjustable Fork Spacing (in.)	8-3/8 to 26-3/4 (OD)
Adjustable Leg Spacing (in.)	49-1/4 to 57-7/8 (OD)
Overall Mast Height (in.)	171-13/16
Drive Motor	DC 24V / 0.7 KW
Lift Motor	DC 24V / 2.0 KW
Battery	(2) 12V / 95 Ah
Battery Charger	DC 24V / 6 amp
Operation Time with Constant Use (hrs.)	3 to 4
Operation Time with Intermittent Use (hrs.)	8
Drive Wheel Qty./Diameter/Width (in.)	(2) 9-7/8 x 3-1/8
Front Wheel Qty./Diameter/Width (in.)	(2) 4 x 2.9
Stabilizer Wheel Qty./Diameter/Width (in.)	(2) 3 x 1-7/16
Wheel Material	Poly-on-Steel
Travel Speed - Loaded (MPH)	2.3
Travel Speed - Unloaded (MPH)	2.5
Battery Depth	11
Battery Width	14
Battery Height	9
Battery Weight	84
Battery Freight Class	70
Battery NMFC Number	60680
Battery NMFC Description	UN2794 BATTERIES WET FILLED WITH ACID

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA