

Steel Adjustable Double Mast Stacker 118 In. Raised Height 3,000 Lb. Capacity Black / Yellow

MODEL S3-118-AA

Ergonomic Solutions / Double Mast Stackers with Powered Drive and Powered Lift

PRODUCT OVERVIEW

The double mast fully powered electric stacker transports loads throughout warehouse facilities quickly and with less effort. High torque drive and lift motor handles heavy duty jobs. Ergonomic handle features lift/lower controls, proprietary safety enhancing emergency reverse function, and horn. The unit includes an electromagnetic disc brake with automatic dead-man feature that activates when user releases the handle. Powered lifter has two batteries, integral battery charger, and a battery level gauge. Horn included.

KEY FEATURES

- Stacker has a bright yellow finish for clear visibility
- Infinite speed adjustment in forward and reverse
- Emergency reverse belly switch instantly reverses direction
- Automatic shut off is applied when handle disengaged

CORE PRODUCT DATA

ASSEMBLED WEIGHT
1920 lbs

ASSEMBLED SIZE
50" W x 76.625" L x 79" H

SHIP WEIGHT
1868 lbs

PACKAGE 1 SIZE
60" W x 80" D x 90" H

COLOR / FINISH
Black / Yellow

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity 0 - 62" (lb.)	3,000
Uniform Capacity 62 - 118" (lb.)	2,500
Service Range (in.)	2-9/16 to 118
Fork Width/Length (in.)	4 x 42
Adjustable Fork Spacing (in.)	7-7/8 to 26-3/4 (OD)
Adjustable Leg Spacing (in.)	41-3/8 to 50 (ID)
Overall Mast Height - Retracted (in.)	79
Overall Mast Height - Extended (in.)	136-13/16
Drive Motor	DC 24V / 1.2 KW
Lift Motor	DC 24V / 3.0 KW
Battery	(2) 12V / 80-95 Ah
Battery Charger	24V / 8 amp
Operation Time with Constant Use (hrs.)	3 to 4
Operation Time with Intermittent Use (hrs.)	8
Travel Speed - Loaded (MPH)	2.8
Travel Speed - Unloaded (MPH)	3.4
Drive Wheel Diameter/Width (in.)	9-7/8 x 4
Front Wheel Qty./Diameter/Width (in.)	(2) 5 x 2-9/10
Stabilizer Wheel Diameter/Width (in.)	5-9/10 x 2
Battery Depth	14
Battery Width	14
Battery Height	10
Battery Weight	112
Battery Freight Class	70
Battery NMFC Number	60680
Battery NMFC Description	UN2794 BATTERIES WET FILLED WITH ACID
Battery Subclass	1
Lithium Battery Configuration	C -- Contained In

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty: 1 Year

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=253>