

Steel Adjustable Spreader Beam 78 In. Length 2,500 Lb. Capacity Blue

MODEL SBM-25

Overhead Lifting / Adjustable Spreader Beams

PRODUCT OVERVIEW

The adjustable spreader beam is ideal for the manufacturing and maintenance facilities. The steel construction keeps the unit durable and strong for a lifetime of use. The beam is shipped with a test certificate.

KEY FEATURES

- Designed to lift and move uneven and awkward loads
- Complies with ASME B30.20-1993 standards
- Includes two lower bails and one upper bail standard for added versatility
- Welded steel construction for heavy duty performance

CORE PRODUCT DATA

ASSEMBLED WEIGHT
119 lbs**ASSEMBLED SIZE**
16.5" W x 78" L x 5" H**SHIP WEIGHT**
178 lbs**PACKAGE 1 SIZE**
29" W x 92" D x 10" H**COLOR / FINISH**
Blue**FREIGHT TYPE**
LTL Palletized**AVAILABILITY** Out of Stock - Please Contact Sales**QUICKSHIP: YES**

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

PRODUCT SPECIFICATIONS

Uniform Capacity (lb.)	2,500
Headroom (in.)	14-3/4
Minimum Spread (in.)	8
Maximum Spread (ft.)	6
Usable Upper Bail Width/Height (in)	2-1/2 x 4-1/2
Usable Lower Bail Width/Height (in.)	1-1/2 x 4-1/2
Upper/Lower Bail Thickness (in.)	3/4
ASME	B30.20-1993
C-Channel Height (in.)	5
Overall Width (in.)	5
Overall Height (in.)	16-1/2
Overall Length (in.)	78

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA

Live product page: <https://www.vestil.com/product.php?FID=572>