

Steel Winch Truck Jib Crane 44 In. Reach 1,000 Lb. Extended Capacity Yellow

MODEL WTJ-4

Overhead Lifting / Winch Operated Truck Jib Cranes



PRODUCT OVERVIEW

This winch operated truck Jib crane lifts items from ground to truck bed height, then rotate into cargo area. Includes telescopic boom design with manual hydraulic hand pump to pivot boom up and down. Manual cable winch to lift and lower loads. Unit comes with one grab hook, one chain slot lock, and one sling hook with latch. Unit is designed for vertical lifting only. Do not use unit for lifting personnel or overhead lifting.

KEY FEATURES

- Powered cable winch makes lifting and maneuvering easy
- Boom telescopes in and out for greater reach and versatility
- 360 Degrees swivel design allows for maximum accessibility
- Pre-drilled base plate makes mounting quick and easy

CORE PRODUCT DATA

ASSEMBLED WEIGHT
145 lbs

ASSEMBLED SIZE
32.875" W x 10.625" L x 57.5" H

SHIP WEIGHT
145 lbs

PACKAGE 1 SIZE
12" W x 65" D x 17" H

COLOR / FINISH
Yellow

FREIGHT TYPE
LTL Palletized

AVAILABILITY Available

QUICKSHIP: YES

Products are sold through Vestil distributor partners. Contact a distributor for current pricing and ordering.

ADDITIONAL PRODUCT VIEWS



PRODUCT SPECIFICATIONS

Uniform Cable Winch Capacity (lb.)	500
Extended Fixed Hook Capacity (lb.)	1,000
Extended Usable Reach (in.)	44
Extended Maximum Hook Height (in.)	86 1/2
Extended Minimum Hook Height (in.)	Zero
Retracted Fixed Hook Capacity (lb.)	2,000
Retracted Usable Reach (in.)	30
Retracted Maximum Hook Height (in.)	77-1/2
Retracted Minimum Hook Height (in.)	13-1/2
Overall Cable Length (ft.)	32
Usable Cable Length (ft.)	24
Cable Diameter (in.)	3/16
Mounting Plate Length (in.)	10-5/8
Mounting Plate Width (in.)	10-5/8
Base Height (in.)	12-1/4
Rotation (degrees)	360
Piston Stroke (in.)	16-3/8
Piston Stroke Per Pump (in.)	1/16
Cable Retracts/Extension Per Crank (in.)	1-1/2
Number of Cranks to Retract/Extend Cable	72
Wire Rope Material	Galvanized Steel
Hook Material	Steel
Hook Opening (in.)	1-3/32
Hook Movement	Rigid
Fasteners Included	No
Mounting Hole Diameter (in.)	11/16

PRODUCT & SHIPPING REFERENCE

Shipping Point: Angola, IN 46703

Warranty:

90 Days

AVAILABLE PRODUCT RESOURCES



SCAN FOR CURRENT PRODUCT DATA